

Cat® C175-16

Diesel Generator Sets




Image shown may not reflect actual configuration

Bore – mm (in)	175 (6.89)
Stroke – mm (in)	220 (8.66)
Displacement – L (in ³)	84.7 (5166.88)
Compression Ratio	16.7:1
Aspiration	TA
Fuel System	Common Rail
Governor Type	ADEM™ A4

Standby 60 Hz kW (kVA)	Mission Critical 60 Hz kW (kVA)	Prime 60 Hz kW (kVA)	Continuous 60 Hz kW (kVA)	Emissions Performance
3100 (3875)	3100 (3875)	2825 (3531)	2600 (3250)	U.S. EPA Stationary Emergency Use Only. (Tier 2)

Features

Cat® Diesel Engine

- Meets U.S. EPA Stationary Emergency Use Only (Tier 2) emission standards
- Reliable performance proven in thousands of applications worldwide

Generator Set Package

- Accepts 100% block load in one step and meets NFPA 110 loading requirements
- Conforms to ISO 8528-5 G3 load acceptance requirements
- Reliability verified through torsional vibration, fuel consumption, oil consumption, transient performance, and endurance testing

Alternators

- Superior motor starting capability minimizes need for oversizing generator
- Designed to match performance and output characteristics of Cat diesel engines

EMCP 4 Control Panels

- User-friendly interface and navigation
- Scalable system to meet a wide range of installation requirements
- Expansion modules and site specific programming for specific customer requirements

Warranty

- 24 months/1000-hour warranty for standby and mission critical ratings
- 12 months/unlimited hour warranty for prime and continuous ratings
- Extended service protection is available to provide extended coverage options

Worldwide Product Support

- Cat dealers have over 1,800 dealer branch stores operating in 200 countries
- Your local Cat dealer provides extensive post-sale support, including maintenance and repair agreements

Financing

- Caterpillar offers an array of financial products to help you succeed through financial service excellence
- Options include loans, finance lease, operating lease, working capital, and revolving line of credit
- Contact your local Cat dealer for availability in your region

Standard and Optional Equipment

Engine

Air Cleaner

- ☐ Single element
- ☐ Dual element

Muffler

- ☐ Industrial grade (15 dB)
- ☐ Residential grade (25 dB)
- ☐ Critical grade (34 dB)

Starting

- ☐ Standard batteries
- ☐ Oversized batteries
- ☐ Standard electric starter(s)
- ☐ Dual electric starter(s)
- ☐ Air starter(s)
- ☐ Jacket water heater

Alternator

Output voltage

- ☐ 480V ☐ 6900V
- ☐ 600V ☐ 12470V
- ☐ 4160V ☐ 13200V
- ☐ 6300V ☐ 13800V
- ☐ 6600V

Temperature Rise **(over 40°C ambient)**

- ☐ 150°C
- ☐ 125°C/130°C
- ☐ 105°C
- ☐ 80°C

Winding type

- ☐ Form wound

Excitation

- ☐ Permanent magnet (PM)

Attachments

- ☐ Anti-condensation heater
- ☐ Stator and bearing temperature monitoring and protection

Power Termination

Type

- ☐ Bus bar
- ☐ Circuit breaker
- ☐ 4000A ☐ 5000A
- ☐ UL ☐ IEC
- ☐ 3-pole
- ☐ Electrically operated

Trip Unit

- ☐ LSI ☐ LSI-G
- ☐ LSIG-P

Control System

Controller

- ☐ EMCP 4.2B
- ☐ EMCP 4.3
- ☐ EMCP 4.4

Attachments

- ☐ Local annunciator module
- ☐ Remote annunciator module
- ☐ Expansion I/O module
- ☐ Remote monitoring software

Charging

- ☐ Battery charger – 20A
- ☐ Battery charger – 35A
- ☐ Battery charger – 50A

Vibration Isolators

- ☐ Rubber
- ☐ Spring
- ☐ Seismic rated

Cat Connect

Connectivity

- ☐ Ethernet
- ☐ Cellular

Extended Service Options

Terms

- ☐ 2 year (prime)
- ☐ 3 year
- ☐ 5 year
- ☐ 10 year

Coverage

- ☐ Silver
- ☐ Gold
- ☐ Platinum
- ☐ Platinum Plus

Ancillary Equipment

- ☐ Automatic transfer switch (ATS)
- ☐ Paralleling switchgear
- ☐ Paralleling controls

Certifications

- ☐ UL 2200 Listed
- ☐ CSA
- ☐ IBC seismic certification
- ☐ OSHPD pre-approval


Note: Some options may not be available on all models. Certifications may not be available with all model configurations. Consult factory for availability.

Package Performance

Performance	Standby		Mission Critical		Prime		Continuous	
Frequency	60 Hz		60 Hz		60 Hz		60 Hz	
Gen set power rating without fan	3100 eKW		3100 eKW		2825 eKW		2600 eKW	
Gen set power rating without fan @ 0.8 power factor	3875 kVA		3875 kVA		3531 kVA		3250 kVA	
Emissions	EPA ESE (Tier 2)		EPA ESE (Tier 2)		EPA ESE (Tier 2)		EPA ESE (Tier 2)	
Performance number	DM8455-08		DM9239-04		DM8706-06		DM8707-04	
Fuel Consumption								
100% load without fan – L/hr (gal/hr)	797.4	(210.7)	797.4	(210.7)	715.1	(188.9)	654.2	(172.8)
75% load without fan – L/hr (gal/hr)	605.1	(159.8)	605.1	(159.8)	561.5	(148.3)	516.8	(136.5)
50% load without fan – L/hr (gal/hr)	473.5	(125.1)	473.5	(125.1)	445.8	(117.8)	419.4	(110.8)
25% load without fan – L/hr (gal/hr)	283.7	(75.0)	283.7	(75.0)	264.2	(69.8)	246.9	(65.2)
Cooling System								
Engine coolant capacity – L (gal)	303.5	(80.2)	303.5	(80.2)	303.5	(80.2)	303.5	(80.2)
Inlet Air								
Combustion air inlet flow rate – m³/min (cfm)	262.6	(9273.3)	262.6	(9273.3)	247.0	(8722.7)	230.9	(8153.2)
Exhaust System								
Exhaust stack gas temperature – °C (°F)	478.1	(892.7)	478.1	(892.7)	460.0	(860.0)	443.9	(831.0)
Exhaust gas flow rate – m³/min (cfm)	688.1	(24296.2)	688.1	(24296.2)	627.6	(22162.0)	572.6	(20217.9)
Exhaust system backpressure (maximum allowable) – kPa (in. water)	6.7	(27.0)	6.7	(27.0)	6.7	(27.0)	6.7	(27.0)
Heat Rejection								
Heat rejection to jacket water – kW (Btu/min)	1355	(77079)	1355	(77079)	1233	(70109)	1146	(65175)
Heat rejection to exhaust (total) – kW (Btu/min)	3086	(175510)	3086	(175510)	2692	(153112)	2464	(140107)
Heat rejection to aftercooler – kW (Btu/min)	481	(27356)	481	(27356)	384	(21817)	343	(19490)
Heat rejection to atmosphere from engine – kW (Btu/min)	181	(10265)	181	(10265)	169	(9592)	164	(9349)
Heat rejection from alternator – kW (Btu/min)	119	(6773)	119	(6773)	109	(6170)	94	(5363)
Emissions* (Nominal)								
NOx mg/Nm³ (g/hp-h)	3107.8	(6.05)	3107.8	(6.05)	3292.8	(6.32)	3246.1	(6.07)
CO mg/Nm³ (g/hp-h)	157.9	(0.35)	157.9	(0.35)	191.2	(0.42)	232.3	(0.50)
HC mg/Nm³ (g/hp-h)	15.2	(0.04)	15.2	(0.04)	16.5	(0.04)	16.1	(0.04)
PM mg/Nm³ (g/hp-h)	10.3	(0.03)	10.3	(0.03)	15.2	(0.04)	15.5	(0.04)
Emissions* (Potential Site Variation)								
NOx mg/Nm³ (g/hp-h)	3729.4	(7.26)	3729.4	(7.26)	3951.3	(7.58)	3895.4	(7.29)
CO mg/Nm³ (g/hp-h)	284.3	(0.63)	284.3	(0.63)	344.2	(0.75)	418.8	(0.90)
HC mg/Nm³ (g/hp-h)	20.3	(0.05)	20.3	(0.05)	21.9	(0.06)	21.4	(0.06)
PM mg/Nm³ (g/hp-h)	14.4	(0.04)	14.4	(0.04)	21.3	(0.05)	21.7	(0.05)

*mg/Nm³ levels are corrected to 5% O₂. Contact your local Cat dealer for further information.

Weights and Dimensions



Dim "A" mm (in)	Dim "B" mm (in)	Dim "C" mm (in)	Dry Weight kg (lb)
6137 (241.6)	2110 (83.1)	2211 (87.0)	19 391 (42,750)

Note: For reference only. Do not use for installation design. Contact your local Cat dealer for precise weights and dimensions.

Ratings Definitions

Standby

Output available with varying load for the duration of the interruption of the normal source power. Average power output is 70% of the standby power rating. Typical operation is 200 hours per year, with maximum expected usage of 500 hours per year.

Mission Critical

Output available with varying load for the duration of the interruption of the normal source power. Average power output is 85% of the mission critical power rating. Typical peak demand up to 100% of rated power for up to 5% of the operating time. Typical operation is 200 hours per year, with maximum expected usage of 500 hours per year.

Prime

Output available with varying load for an unlimited time. Average power output is 70% of the prime power rating. Typical peak demand is 100% of prime rated kW with 10% overload capability for emergency use for a maximum of 1 hour in 12. Overload operation cannot exceed 25 hours per year.

Continuous

Output available with non-varying load for an unlimited time. Average power output is 70-100% of the continuous power rating. Typical peak demand is 100% of continuous rated kW for 100% of the operating hours.

Applicable Codes and Standards

AS 1359, CSA C22.2 No. 100-04, UL 142, UL 489, UL 869, UL 2200, IBC, IEC 60034-1, ISO 3046, ISO 8528, NEMA MG1-22, NEMA MG1-33, 2014/35/EU, 2006/42/EC, 2014/30/EU and facilitates compliance to NFPA 37, NFPA 70, NFPA 99, NFPA 110.

Note: Codes may not be available in all model configurations. Please consult your local Cat dealer for availability.

Data Center Applications

- ISO 8528-1 Data Center Power (DCP) compliant per DCP application of Cat diesel generator set prime power rating.
- All ratings Tier III/Tier IV compliant per Uptime Institute requirements.
- All ratings ANSI/TIA-942 compliant for Rated-1 through Rated-4 data centers.

Fuel Rates

Fuel rates are based on fuel oil of 35° API [16°C (60°F)] gravity having an LHV of 42,780 kJ/kg (18,390 Btu/lb) when used at 29°C (85°F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal.)

www.cat.com/powergeneration

©2020 Caterpillar

All rights reserved.

Materials and specifications are subject to change without notice. The International System of Units (SI) is used in this publication.

CAT, CATERPILLAR, LET'S DO THE WORK, their respective logos, "Caterpillar Corporate Yellow", the "Power Edge" and Cat "Modern Hex" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.